













Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl				
	PE-Rohre, getempert, in Stangen zu 5 m		<b>363.045</b>	56			Bogen 90°					
		<b>379.000</b>	32	<b>364.045</b>	63			<b>379.055</b>	32			
		<b>360.000</b>	40	<b>365.045</b>	75			<b>360.055</b>	40			
		<b>361.000</b>	50	<b>366.045</b>	90			<b>361.055</b>	50			
		<b>363.000</b>	56	<b>367.045</b>	110			<b>363.055</b>	56			
		<b>364.000</b>	63	<b>368.045</b>	125			<b>364.055</b>	63			
		<b>365.000</b>	75	<b>369.045</b>	160			<b>365.055</b>	75			
		<b>366.000</b>	90		Bogen 45° mit langem Schenkel			<b>366.055</b>	90			
		<b>367.000</b>	110					<b>367.055</b>	110			
		<b>368.000</b>	125					<b>368.055</b>	125			
		<b>369.000</b>	160					<b>369.055</b>	160			
		<b>370.000</b>	200									
		<b>371.000</b>	250									
<b>372.000</b>	315											
	PE-Rohre verstärkt, für erhöhten Unterdruck bei Pluvia- Dachentwässerungssystem			Bogen 15° mit großem Radius		Bogen 90° mit engem Radius						
		<b>370.015</b>					200	<b>366.876</b>	90			
		<b>371.015</b>					250	<b>367.876</b>	110			
		<b>372.015</b>					315					
		<b>370.050</b>					200		Bogen 30° mit großem Radius		Anschlusswinkel 88,5°	
		<b>371.050</b>					250					<b>361.088</b>
<b>372.050</b>	315	<b>363.088</b>	56									
	Tragschalen, in Stangen zu 3 m		<b>370.030</b>	200		<b>364.088</b>	63					
		<b>360.850</b>	40	<b>371.030</b>	250		<b>365.088</b>	75				
		<b>361.850</b>	50	<b>372.030</b>	315		<b>366.088</b>	90				
		<b>363.850</b>	56		Bogen 45° mit großem Radius	<b>367.088</b>	110					
		<b>364.850</b>	63				Putzstück 90° mit Verschlusskappe					
		<b>365.850</b>	75					<b>364.451</b>	63			
		<b>366.850</b>	90					<b>365.451</b>	75			
		<b>367.850</b>	110					<b>366.451</b>	90			
		<b>368.850</b>	125					<b>367.451</b>	110			
		<b>369.850</b>	160	<b>368.451</b>	125							
		<b>370.850</b>	200		Bogen 90° mit großem Radius	<b>369.451</b>	160					
		<b>371.850</b>	250									
		<b>372.850</b>	315									
	Bogen 45°		<b>370.055</b>	200								
		<b>360.045</b>	40	<b>371.055</b>	250							
		<b>361.045</b>	50	<b>372.055</b>	315							



Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl							
364.561	63/50			Steckmuffe mit Dichtung				Bundbüchse							
364.566	63/56														
365.558	75/40														
365.561	75/50														
365.566	75/56														
365.571	75/63														
366.561	90/50														
366.566	90/56														
366.571	90/63														
366.576	90/75														
367.558	110/40														
367.561	110/50														
367.566	110/56														
367.571	110/63														
367.576	110/75														
367.581	110/90									Hosen-T, 60°			Verschlusskappe komplett		
368.561	125/50														
368.566	125/56														
368.571	125/63														
368.576	125/75														
368.581	125/90														
368.586	125/110														
369.586	160/110														
369.588	160/125														
369.591	160/140														
	Elektroschweißmuffe			Langmuffe mit Dichtung für waagrechte und senkrechte Montage				Verschlusskappe komplett							
														379.791	32
														360.700	40
														361.700	50
														363.700	56
														364.700	63
									365.700	75					
									366.700	90					
									367.700	110					
									368.700	125					
369.700	160														
370.700	200														
371.700	250														
372.700	315														
	Thermoschweißmuffe			Verschraubung, komplett				Verschlusskappe komplett							
									379.740	32					
									360.740	40					
									361.740	50					
									363.740	56					
									364.740	63					
									365.740	75					
									366.740	90					
									367.740	110					
													PE-Wand-WC-Bogen 90° für senkrechte Montage		
360.771	40														
361.771	50														
363.771	56														
364.771	63														
365.771	75														
366.771	90														
367.771	110														
368.771	125														
369.771	160														
				PE-Wand-WC-Bogen 90°, rechts für waagrechte Montage											
366.925	90/90														
367.925	110/90														
367.792	110/110														
366.913	90/90														
367.913	110/90														
367.901	110/110														
									PE-Wand-WC-Bogen 90°, links für waagrechte Montage						
366.914	90/90														
367.914	110/90														
367.902	110/110														

Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl	Art.-Nr.	Dimension	Anzahl
	PE-Wand-WC-Doppelbogen 90° für senkrechte Montage			Steckdichtungen zu Siphonanschlusswinkel			PE-Anschweißenden mit Innengewinde	
<b>367.923</b>	110/90		<b>152.498</b>	40 × 32 mm		<b>360.719</b>	40/ 1/2"	
<b>367.903</b>	110/110		<b>152.495</b>	46 × 32 mm		<b>360.720</b>	40/ 3/4"	
			<b>152.496</b>	46 × 40 mm		<b>360.721</b>	40/1"	
			<b>153.564</b>	58 × 32 mm		<b>361.719</b>	50/ 1/2"	
			<b>153.565</b>	58 × 40 mm		<b>361.720</b>	50/ 3/4"	
			<b>153.566</b>	58 × 50 mm		<b>361.721</b>	50/1"	
	PE-Wand-WC-Doppelbogen 90° für waagrechte Montage			Übergang Geberit/ Guss, muffenlos		<b>361.722</b>	50/1 1/4"	
<b>367.485</b>	110/90		<b>359.268</b>	125/135		<b>361.723</b>	50/1 1/2"	
<b>367.904</b>	110/110		<b>370.738</b>	200/212		<b>363.724</b>	56/2"	
			<b>371.738</b>	250/274		<b>364.724</b>	63/2"	
			<b>372.738</b>	315/326		<b>365.725</b>	75/2 1/2"	
	Siphonanschlussbogen			Bride Geberit/Guss muffenlos DN 70			Brandschutzmanschette RS90Plus EN	
<b>361.080</b>	50/50		<b>359.434</b>	75-76		<b>348.300</b>	40-56	
<b>363.083</b>	56/50					<b>348.301</b>	63-75	
<b>363.080</b>	56/56					<b>348.302</b>	90	
<b>364.084</b>	56/63					<b>348.303</b>	110	
	Dopplebogen 2 × 90°			Chromstahl Stützring, als Verstärkung zum Einschlagen ins PE-Rohrende		<b>348.304</b>	125/135	
<b>361.498</b>	50/50		<b>359.455</b>	56		<b>348.305</b>	160	
			<b>359.456</b>	63		<b>348.306</b>	200	
	Steckdichtungen zu Siphonanschlussbogen und Doppelbogen		<b>359.457</b>	75			Rohrbelüftungsventil	
<b>152.682</b>	44/32		<b>359.458</b>	90		<b>359.900</b>	32-63	
<b>152.796</b>	44/40		<b>359.459</b>	110				
<b>152.689</b>	50/32		<b>359.464</b>	160			Rohrbelüftungsventil	
<b>152.690</b>	50/40					<b>310.006</b>	PE 75-110	
<b>152.691</b>	57/32			PE-Anschweißende mit Außengewinde				
<b>152.692</b>	57/40		<b>361.726</b>	50/1 1/4"				
<b>152.693</b>	57/50		<b>361.727</b>	50/1 1/2"				
	Siphonanschlusswinkel		<b>363.728</b>	56/2"				
<b>360.061</b>	40/46		<b>364.728</b>	63/2"				
<b>361.065</b>	50/58		<b>365.729</b>	75/2 1/2"				
<b>363.065</b>	56/58							